

DIAMAPRO® SYSTEMS DCP-PRO



The DCP-Pro's efficient battery management and ergonomic design ensures maximum comfort, and uninterrupted performance throughout the workday.

Diamapro Systems' DCP-Pro dual component pump is equipped with two power options. The pump can be easily plugged into any 110V outlet or it can be switched to its battery powered option. The DCP-Pro features an approximate eight hour total 24V battery system and a built-in battery life indicator. This pump ensures all-day productivity without interruptions.

- Dual ten-gallon molded plastic tanks, offer extended operational time before requiring a refill. Clean-up is made effortless with the DCP-Pro's built in integrated washout system with a three gallon cleaning fluid tank.
- The DCP-Pro is designed for operator comfort by enabling a stand-up application, sparing users from having to kneel.
- It includes an application wand with an adjustable flow grip handle, elbow brace, and customizable height adjustments to suit various operators.
- The DCP-Pro's robust frame, casters, handles and components are built to stand up to the harshest job sites.

Perfect for use on:

- Large joint filling floor projects
- Polyurea joint filler projects
- Epoxy joint filler projects
- Application of some polyaspartic coatings

SPECIFICATIONS:

| | |
|------------------------|-------------------------------------|
| Weight | 232 LBS |
| Dimensions (L x H x W) | 50" X 42" X 23" |
| Motor (Torque) | 15.6 Nm (140in-lb) |
| Pumps | Internal Gear Pump |
| Tanks | 2 X 10 Gallon |
| Power | 110V (Wall Power) |
| Battery | 24V Battery |
| Control | Adjustable Wand with Variable Speed |
| Ratio | 1:1 |
| Flow Rate | 0-0.3 GPM |
| Wash Out Tank | 3 Gallons |



PAIRS WELL WITH
DIAMAPRO SYSTEMS®
DIAMA-JOINT FILL



DIAMAPRO® SYSTEMS DCP-PRO



CONTROLLED MATERIAL FLOW GRIP



ERGONOMICALLY DESIGNED APPLICATION WAND



BATTERY LIFE INDICATOR AND EASY FLIP ELECTRICAL SYSTEM



DUAL ON-BOARD 24V BATTERIES



3 GALLON INTEGRATED WASHOUT SYSTEM



2 BALL VALVES TO FLUSH PUMP LINES



LARGE TANK LIDS FOR EASY ACCESS



VIEW PORTS ON TRANSLUCENT TANKS TO MONITOR LIQUID LEVELS



USE BATTERY POWER OR WALL OUTLET POWER



QUICK JOINT FILLING VS. CARTRIDGE APPLICATION

Why choose the DiamaPro Systems' DCP-Pro Dual Component Pump

- Reduce labor costs by significantly increasing application speed on concrete floor projects
- Reduce material waste with a controlled material flow grip
- Easiest pump on the market to clean
- Integrated three gallon tank washout system. Just flip 2 ball valves to flush the pump lines
- Easy flip electrical system 110V or Battery with 8 hour battery life indicator
- Ergonomically designed application wand has an adjustable flow grip handle, elbow brace, and customizable height adjustments to suit various operators
- Production rate to 5,000 lineal joint filling feed per day
- Quick joint filling vs. cartridge application
- Twin tanks each hold 10 gallons of product
- Translucent tanks allow the operator to monitor liquid levels
- Large tank lids allow easy access
- Dispenses in a 1:1 ratio
- Built Jobsite Tough with a heavy duty frame and casters
- Easy grip handles for job site maneuverability



**NIAGARA
MACHINE, INC.**

ESTABLISHED 1954

www.niagamachine.com
800-622-2048

SIX SHOWROOM / WAREHOUSE LOCATIONS, EIGHT REPAIR CENTERS, NINE SALES LOCATIONS

325 West Front
Erie, PA 16507
814-455-8838

4833 Sandy Porter Rd.
Unit D
Charlotte, NC 28273
704-329-5701

435 Oehler Place
Carlstadt, NJ 07072
201-758-5422

500 South Broadway
Gloucester City, NJ 08030
856-742-7200

889 S. Charles Richard Beall Blvd.
Suite 305
Debary, FL 32713
386-320-0406

2122 113th St.
Grand Prairie, TX 75050
682-320-8153